

TECHNICAL DATA SHEET**en****Name of product:****FAXE Oilotion 0246**

| | |
|-------------------------|---|
| Type of product: | Waterbased oil care product based on vegetable oils and contains wax. |
| Application: | FAXE Oilotion is especially suitable for wooden floorings, which are fabric oil treated or basic treated with a FAXE Oil. FAXE Oilotion is not suitable for lacquered and artificial surfaces. For this purpose is FAXE GOLak Care recommended. |
| Properties: | FAXE Oilotion is developed for refreshing and maintenance of oiled floorings. The product is fast drying and the floor will soon be ready for use. FAXE Oilotion provides the floor with oil and maintains it. Gives a transparent, protecting and liquid resistant layer on the surface, which makes it easy to maintain. On natural oiled surfaces FAXE Oilotion will highlight and maintain the depth of the wood and the golden glow in the wood. |

| | |
|-----------------------|---|
| Pre-treatment: | <p>Before application remove any old conditioner and stubborn dirt using FAXE Intensive Cleaner. Dilute FAXE Intensive Cleaner 1:20 and clean the floor. Wash hereafter with clean water. Let the floor dry for approx. 1-2 hours.</p> <p>* Shake the can a couple of times and pour out the required quantity in a suitable container or directly on the floor.</p> <p>* If the can with FAXE Oilotion is left untouched for a longer period, then shake the closed can a few times before using it again.</p> <p>* Apply an even, thin layer with the grain. Work wet-in-wet and not over areas which already has dried.</p> <p>* If there are areas, which absorb a lot of material, apply more FAXE Oilotion, while the surface is still wet.</p> <p>* If there are areas, where a lot of material creates pools on the surface, even out the material for more uniform result.</p> |
|-----------------------|---|

Application:

| Method: | Recommended viscosity: | Thinner: |
|-------------------|-------------------------------|--------------------------|
| Microfibre roller | No thinning required | Do not polish the floor. |
| Lambswool swab. | No thinning required | Do not polish the floor. |
| Sponge | No thinning required | Do not polish the floor. |

Drying:

| | Drying time | Film thickness - dry |
|-------------|--------------------|---|
| Dry to use | 3-4 hours 20 °C | - |
| Fully cured | 3 day(s) 20 °C | The floor must be fully cured before use. |

System Specification:

* If a second application is required, this can be done after 3-4 hours.

* Do not polish the floor after FAXE Oilotion has been applied.

Cleaning/maintenance:

Daily maintenance of wood treated with FAXE Oilotion only requires vacuum-cleaning. When the wood gets dirty it is easily cleaned with FAXE Active Care or FAXE Wooden Floor Soap.

| | |
|--------------------|--|
| Coverage: | Theoretical: 20 m ² /ltr. |
| Storage: | Frostfree, cool, and closed. |
| Shelf-life: | 12 Months in an unopened container |
| Cleaning: | The tools should be cleaned with water. Do not clean newly oiled surfaces the first 3 days after application. |

VOC explanation: Product marking: 2004/42/IIA(X)(YY)ZZZ EU directive number: 2004/42/
Directive annex number: IIA
Product subcategory: (X)
VOC content limit value g/l 2010: (YY)
Maximum VOC Content in this product when ready for use, g/l: ZZZ

Note: It is always recommended to make a small test area to check surface, adhesion and colour tone.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk